



### Key Features

- 3.5 hours of run time
- Enclosed on-board fully automatic charging capability
- 28" burnishing pad
- Heavy duty 3.25 horsepower DC motor provides maximum performance
- Self propelled transaxle operation allows for effortless operation
- Supervisor lock-out key

### Safety

- Complete re-settable thermal overload protection
- "Dead Man" operator automatic shutdown protection
- Poly-Rotational molded housing acts as an environmental safety bumper
- Machine operates at 71db for quiet operation

### Markets

- Retail
- Building Service Contractor
- Health Care
- Commercial
- Education

### Accessories/Options

- Active dust control
- H.E.P.A filtration

### General Overview

- Most productive walk behind battery burnisher on the market
- The Lumina 28 gives safe high performance results with out excessive noise or exhaust fumes
- Simple operator control interface
- Heavy duty 11 gauge epoxy coated steel chassis for long life cycle capability
- Burnishes up to 33,633 square feet per hour

### Productivity

- Up to 3.5 hour run time
- 1600 rpm pad speed produces a quick shine with high productivity
- Available with active dust control and H.E.P.A capability
- The Lumina 28 will burnish over 100,000 square feet on one battery charge

### Ease of Use

- Simple 2 button control panel
- Universal operating symbols allow for easy cross training
- On-board fully automatic smart charger
- Easy battery maintenance access
- Easy pad removal

Specifications	
Model	M28036TDQP
Frame/Housing	Rotationally molded polyethylene housing/11 gauge steel frame
Coating	Electrostatically applied epoxy coat
Switches	Master on/off key switch/Master E -Stop switch
Circuit Breakers	Electronic thermal overload breakers protect motors and circuitry
Power Supply	Standard (3) 12 volt 370 AH Deep Cycle
Charger	36volt, 25amp, high frequency automatic charger
Motor	3.75 HP 66 Frame 36 volt DC
Pad Size	28" (71 cm) diameter
Pad Pressure	Electro-Mechanical pad pressure adjustment; visual monitor shows burnishing performance
Pad Speed	1600 RPM
Weight	With batteries 970lbs. (440kg)
Dust Control	Active dust control optional/ H.E.P.A filter optional
Wheels front	8" cast aluminum w/urethane tread non -marking
Wheels rear	3" swivel caster, non -marking
Dimensions LxWxH	66"x30"x44" (167x76x111)
Propulsion	Variable speed transaxle

Specifications subject to change without notice.

MinutemanVac.com is a factory authorized outlet of Minuteman International

8248 West Doe Avenue | Visalia, CA 93291 | Phone: 1.800.637.6606 | Fax: 559.651.1320

Come Visit Our Website at  
[www.minutemanvac.com](http://www.minutemanvac.com)  
 a division of Enviro Safety Products