

Specifications	H20	H26	H30
Cleaning path width	20 in (51 cm)	26 in (65 cm)	30" (76 cm)
Squeegee width	33 in (84 cm)	35.4 in (90 cm)	43 in (110 cm)
Theoretical productivity (BD)	15,000 ft ² /hr (1,394 m ²)	N/A	N/A
Theoretical productivity (TD)	27,280 ft ² /hr (2,534 m ²)	35,464 ft ² /hr (3,294 m ²)	40,920 ft ² /hr (3,802 m ²)
Working speed (BD)	1.7 mph (2.7 km per hr)	N/A	N/A
Working speed (TD)	3.1 mph (5 km per hr)	3.1 mph (5 km per hr)	3.1 mph (5 km per hr)
Rated voltage	24 volts	24 volts	24 volts
Vacuum flow	65 cfm (110 m ³ /hr)	65 cfm (110 m ³ /hr)	65 cfm (110 m ³ /hr)
Vacuum waterlift	45 inches (112mbar)	65 inches (162 mbar)	65 inches (162 mbar)
Vacuum power	.60 HP (450 W)	.86 HP (640 W)	.86 HP (640 W)
Drive motor power (TD)	1/5 HP (150 W)	.42 HP (313 W)	.70 HP
Brush type	Disc	Disc	Disc
Brush motor(s) power	.75 HP	.75 HP (2)	.75 HP (2)
Number of brushes	1	2	2
Brush RPM	180 RPM	180 rpm	180 rpm
Aqua-Stop equipped	Yes	Yes	Yes
Solution capacity	12 Gal (45 liters)	19 Gal (72 liters)	23 Gal (87 liters)
Recovery capacity	13 Gal (49 liters)	19.5 Gal (74 liters)	23 Gal (87 liters)
Weight with batteries (BD)	313 lbs (142 kg)	N/A	N/A
Weight without batteries (BD)	203lbs (92 kg)	N/A	N/A
Weight with batteries (TD)	372 lbs (169 kg)	677 lbs (307 kg)	915 lbs (415 kg)
Weight without batteries (TD)	238 lbs (108 kg)	346 lbs (157 kg)	470 lbs (213 kg)



- Sound Level ≤ 66dBs
- Maintenance Free Gel Batteries Available
- One Button Operation
- Aqua-Stop Feature Available
- Tool Free Brush Removal
- Tool Free Squeegee Removal
- Anti-microbial Rotomolded Recovery Tank

Please visit www.minutemanintl.com for more information on our Green Features.

Not Just Clean, It's Green.



H Series

Walk-Behind Scrubber Hospital Series